



AquaAccess

Barrier Free Bi-Level, Wall Mounted Water Cooler, 8 GPH

SUGGESTED SPECIFICATIONS

Model A112108S is a self-contained, vandal resistant bi-level pressure water cooler that shall deliver a minimum of **8.0 GPH** (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90°F (32.2°C) ambient. Unit shall be activated from both front and side push bars using less than 5 pounds of force. Bubblers shall be polished stainless steel with an integrally designed non-squirt feature and operate on water pressure range of 20-105 psig. Tops shall be constructed from 304 stainless steel and have an integral drain. Cabinets shall be Granite powder coated on galvanized or stainless steel. Evaporator shall be an insulated, tube on tank. Cooling system shall use R-134a refrigerant and be capillary tube controlled. An adjustable thermostat with an off position shall control the refrigeration system. Unit shall adhere to ANSI A117.1 and Americans with Disabilities Act of 1990 frontal approach and protruding objects requirements, **Child ADA** parallel and frontal approach and ANSI/NSF 61, Section 9. Unit shall be listed by Underwriters Laboratories for both the US and Canada, compliant to the Air Conditioning and Refrigeration Institute Standard 1010.

Standard Model:
A112108S

Stainless Steel Model:
A112408S



Model A112408S Shown

STANDARD FEATURES

- Both Child and Adult ADA Compliant (when properly installed)
- Granite powder coated apron and one-piece bottom wrapper
- Polished stainless steel, lead-free, anti-rotation non-squirt bubblers
- Copper tube on stainless steel tank evaporator
- 100 mesh inlet strainer
- Vandal resistant screws

Model Number	GPH*	Rated Watts	Full Load Amps	Approx. Shipping Weight
A112108S	8.0	400	4.8	90 lbs.
A112408S	8.0	400	4.8	90 lbs.

* GPH of 50°F water at 90°F ambient room temperature and 80°F inlet water temperature
Compressor motor operates on 115 Volt / 60 Hz single phase.

OPTIONAL ACCESSORIES (additional costs)

- CSC3 Concealed support carrier
- GF1 Glass filler with lever handle
- RBL Reverse bi-level
- SK Skirt kit, granite, for upper unit
- SK1 Skirt kit, stainless steel, for upper unit
- SO Sensor operated
- WB2 Wall bezel, stainless steel
- WF1 1500 gallon capacity, NSF 42+53, 1 micron lead reduction filter
- 220V 220 volt / 50 Hz compressor (€€)
- "4" All stainless steel (Use model A112408S)

Custom color finishes available upon request

Acorn Aqua™ assumes no responsibility for use of void or suspended data. © Copyright 2009 Acorn Aqua™, City of Industry, CA, A Division of Acorn Engineering Company. Please visit www.acornaqua.com for most current specifications.

Submittal # **A112108S**
3/31/09

COMPLIES WITH STANDARDS



Test rating conditions are compliant with ARI 1010.



Member of Acorn Family of Companies

ACORN AQUA
15125 Proctor Avenue
City of Industry, CA
91746 U.S.A.
Phone 800-591-9360
626-336-4561
Fax 626-855-4894
www.acornaqua.com

